

Snow Products





Blower & Power Pack



Available with the following Quick Tach:

- Universal Skidsteer
- Euro (ALO)
- JD 440/540 Combination

Must be specified at time of order.



Meteor - Loader Mount



Models	SBLM66	SBLM76	SBLM86
HP - Minimum	40 HP	40 HP	40 HP
Cutting Width	66"	76"	86"
Cutting Edge	3/8" x 3"	3/8" x 3"	3/8" x 3"
Skid Shoes	3/8" x 1-1/2"	3/8" x 1-1/2"	3/8" x 1-1/2"
Auger Tube	3-1/2" OD	3-1/2" OD	3-1/2" OD
Auger Flighting	5/16 x 2-1/4	5/16 x 2-1/4	5/16 x 2-1/4
Auger Diameter	19"	19"	19"
Roller Chain	#60	#60	#60
Hitch Plate	Quick-tach	Quick-tach	Quick-tach
Chute Rotation	Hydraulic	Hydraulic	Hydraulic
Chute Diameter	12"	12"	12"
Main Body Height	31"	31"	31"
Chute Deflector	Hydraulic	Hydraulic	Hydraulic
Fan Diameter	26"	26"	26"
Fan Depth	8"	8"	8"
Auger Drive	Hydraulic	Hydraulic	Hydraulic
Fan Drive	Hydraulic	Hydraulic	Hydraulic



Meteor - Single Auger



MK Martin's Meteor series 3PH snowblowers are built to get your work off the ground with durable performance and high-capacity design. The Meteor is available in a range of models for 12 HP compact tractors to 175 HP farm tractors.

Models	SB48	SB54	SB60	SB68
HP (Rec.)	12 HP	15 HP	20 HP	30 HP
Cutting Width	48"	54"	60"	68"
Cutting Edge	1/4 x 1-1/2	3/8 x 1	3/8 x 1	3/8 x 1
Auger Diam.	12"	14"	14"	14"
Fan Diam.	19"	21"	21"	21"
Chute Diam.	7"	8"	8"	10"
Chute Rotation (Man/Hyd)	Std/Opt	Std/Opt	Std/Opt	Opt/Opt
Chute Deflector (Man/Hyd)	Std/NA	Std/Opt	Std/Opt	Std/Opt
Main Body Height	22.5"	25"	25"	29"
3PH Mount	CAT. 1	CAT. 1	CAT. 1	CAT. 1
Weight (LBS.)	266	366	396	506

Meteor - Single Auger



Features

- Gearbox
- High Tensile Steel Ribbon
- Chute Rotation
- 3PH Quick Attach Compatible

Models	SB72	SB75	SB87	SB97
HP (Rec.)	35 HP	50 HP	60 HP	75 HP
Cutting Width	72"	75"	87"	97"
Cutting Edge	3/8 x 1	1/2 x 1-1/2	1/2 x 2	1/2 x 2
Auger Diam.	14"	15"	19"	19"
Fan Diam.	21"	23"	27"	27"
Chute Diam.	10"	10"	12"	12"
Chute Rotation (Man/Hyd)	Opt/Opt	Opt/Opt	Opt/Opt	Opt/Opt
Chute Deflector (Man/Hyd)	Std/Opt	Std/Opt	Std/Opt	Std/Opt
Main Body Height	29"	29"	36"	36"
3PH Mount	CAT. 1	CAT. 1 & 2	CAT. 2	CAT. 2
Weight (LBS.)	540	748	1,034	1,106



Meteor - Double Auger



Models	SB87D	SB97D	SB108D	SB120D
HP (Rec.)	60 HP	100 HP	125 HP	200 HP
Cutting Width	87"	97"	108"	120"
Cutting Edge	1/2 x 2	1/2 X 6*	1/2 x 6*	1/2 x 6*
Auger Diam.	15" (x2)	19" (x1) 15" (x1)	19" (x1) 15" (x1)	23" (x1) 15" (x1)
Fan Diam.	27"	32"	32"	36"
Chute Diam.	12"	13"	13"	13"
Chute Rotation (Man/Hyd)	Opt/Opt	NA/Std	NA/Std	NA/Std
Chute Deflector (Man/Hyd)	Std/Opt	Std/Opt	Std/Opt	Std/Opt
Main Body Height	36"	43"	43"	47"
3PH Mount	CAT. 2	CAT. 2 & 3	CAT. 2 & 3	CAT. 2 & 3
Weight (LBS.)	1,161	1,900	1,980	3,010
Opt. 1000 RPM	-	Yes	Yes	Yes

PTO Options

Models	HP	RPM
97D/108D	100-125	540
97D175/108D175	125-175	540
97D1.75/1081.75	1 3/4 20 Tractor End	1,000
97DF/108DF	1 3/8 21 Tractor End	1,000
SB120D	150-200	540
SB120 D 1.75	1-3/4 20 Tractor End	1,000
SB120DF	1-3/8 21 Tractor End	1,000

Meteor - Pull Type



Models	SB68 P/T	SB75 P/T	SB87 P/T
HP (Rec.)	35 HP	50 HP	60 HP
Cutting Width	69"	75"	87"
Cutting Edge	3/8 x 1	1/2 x 1 1/2	1/2 x 2
Auger Diam.	14"	15"	19"
Fan Diam.	21"	23"	27"
Chute Diam.	10"	10"	12"
Chute Rotation (Man/Hyd)	Manual or Hydraulic (opt.)	Manual or Hydraulic (opt.)	Manual or Hydraulic (opt.)
Chute Deflector (Man/Hyd)	Std./Opt. 6" cyl.	Std./Opt. 8" cyl.	Std./Opt. 8" cyl.
Main Body Height	25"	29"	36"
3PH Mount	CAT. 1	CAT. 1 & 2	CAT. 2
Weight (LBS.)	671	748	1,034



Optional Equipment

- Hydraulic Scraper
- Manual Rear Life Blade
- Hydraulic Lift Option



Features & Options



3PH / Quick Attach

All models are built standard with 3 point hitches in Category 1 or Category 2, and are completely compatible with Quick Attach.



1000 RPM PTO Kit

Available on the 97 and 108 models, a kit is available to allow larger tractors to run at 1000 RPM PTO. The 1000 RPM Kit also raises the input shaft to allow the PTO shaft to run at a lesser angle on larger tractors increasing the efficiency and life of the driveline components.



Gear Box

The heart of Meteor's power train is the time-proven Comer gearbox.



Five Blade Fan

The Meteor five blade fan is ruggedly designed and built to quickly and consistently blow the snow out of the chute.



High Tensile Steel Ribbon Flighting


To make sure you get the longest dependable service from your blower all Meteors have the highest quality High Tensile Steel Ribbon flighting on the auger providing strength to move the snow to the fan.



Skid Shoes

Adjustable skid shoes are included with all snow blowers to protect your surface and your blower.

Features & Options




Chute Rotator

Meteor Snow Blower chute rotators come in manual (crank), hydraulic (orbital motor), and electric.



Multi-Hinged Deflector

Meteor's Multi Hinged Deflector provides you with finer control over where your snow is blown.



Truck Loading Chute

The extendible chute makes placing snow higher on the pile or into a truck easy and virtually spill free.



Chute Deflector

Exit chute deflectors are available in manual or hydraulic (optional).



Meteor - Skidsteer



Hydraulic Meteor Snow Blowers for Skid Steer Loaders feature one piece side plate construction for added strength and rigidity. They also feature an offset chute for better operator vision.

Models	SSB62	SSB66	SSB76	SSB86	SSB96
Cutting Edge (Bolt-On)	1/2 x 4	1/2 x 4	1/2 x 4	1/2 x 4	1/2 x 4
Cutting Width	62"	66"	76"	86"	96"
Auger Diam.	19"				
GPM (min)	14	14	14	30	30
Mounting	Universal Skidsteer Attach				
Chute Rotation	Hydraulic				
Chute Diam.	11"				
Main Body Height	31"				
Chute Deflector (Man/Hyd)	Std/Opt				
Fan Diam.	26"				
Weight (LBS.)	900	925	950	975	1,025

Flow Rates	Code	Flow Rates	Code
14-17 GPM	A	23-26 GPM	C
18-20 GPM	B	27-33 GPM	C+
20-22 GPM	B+	33-40 GPM	D

Code "D" high flow package is recommended on the SSB 96.