

X1.25

24 Engine HP

McCORMICK



Tractor Model		X1.25	X1.25H
Rated Engine Power	HP (kW)	24 (18) @ 2600 RPM	
Rated PTO Power	HP (kW)	21 (15) @ 2600 RPM	18 (13) @ 2600 RPM
Engine Type		1.2 liter, liquid cooled, 3-cylinder diesel, EPA Tier 4	
Aspiration		Natural, with dual element air cleaner	
Engine Preheater		12v glow plug	
Fuel Capacity	gal (liters)	6.23 (23.6), under hood	
Main Clutch		Dry single disc, operated via left side foot pedal	
Transmission Type		6 x 2 sliding mesh	2-range hydrostatic (HST)
Transmission Controls		Left and right hand levers	Side-by-side pedals; cruise control
Differential Lock		Mechanical	
Rear Brakes		Wet disc brakes with suspended R and L pedals	
Front Axle Type		4wd with mechanical engagement	
Rear PTO Type		540 RPM, live transmission driven	
Mid PTO		Standard, 2500 RPM	
Hydraulic System	gpm (lpm)	7.7 (29.1) flow, open center system	
Loader Joystick		Mounted to loader sub frame	
Steering		Hydrostatic power steering	
3-point Type		Category I with position control	
3-point Lift Capacity	lb (kg)	1,500 (3369) at ball ends	
Operator's Area		Right and left entry, folding ROPS	
Seat and Steering		Adjustable vinyl seat; fixed steering	
Overall Length	in (mm)	106 (2700)	
Wheelbase	in (mm)	60 (1530)	
Height Over ROPS	in (mm)	88 (2240)	
Base Weight	lb (kg)	1,810 (3990)	

Loader Model		125C
Max. Lift Height		84.2
Under Level Bucket	in (mm)	(2140)
Lift Capacity		1,060
to Max. Height at Pivot Pin	lb (kg)	(2335)
Breakout Force		1,840
19.5" Forward of Pivot	lb (kg)	(4055)
Loader Attachment		Quick attach
Bucket Level Indicator		Standard
Bucket Size	in (mm)	48 (1220)
Bucket Attachment		Pin type
Compatible Tractor		X1.25, X1.25H



Belly Mower Model		BM60
Cutting Width	in (mm)	60 (1520)
Cutting Height	in (mm)	1.1-3.3 (28-84)
Height Adjustment		3-point lift controls
Number of blades		3
Drive System		Belt drive from mid PTO

McCormick North America

2590 Breckinridge Blvd. / Duluth, GA 30096
(866) 327 - 6733 / www.McCormickNA.com

McCormick and McCormick Logo are registered trademarks of McCormick International USA, Inc. in the U.S. and/or other countries. International Harvester and Farmall are trademarks of CNH America LLC. © 2015 McCormick International USA, Inc. All Rights Reserved. The standard and optional equipment and the availability of individual models might vary from one country to the next. McCormick International USA, Inc. reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. While every effort is made to ensure that the specifications, descriptions, and illustrations in this brochure are correct at the time of printing, these are also subject to change without prior notice. Illustrations might show optional equipment, and might not show all standard equipment.

X1

35 to 55 Engine HP

McCORMICK



Tractor Model		X1.35	X1.45	X1.45C	X1.45HC	X1.55HC
Rated Engine Power	HP (kW)	35 (26)	47 (35)	47 (35)	47 (35)	55 (41)
Rated Engine Speed		2600 RPM				
Rated PTO Power	HP (kW)	29 (21)	42 (31)	42 (31)	42 (31)	47 (35)
Engine Type		3-cyl. diesel	4-cylinder diesel			
Displacement		1.7 L	2.3 L			
Aspiration		Natural, with dual element air cleaner				Turbocharged
Emissions System		EPA Tier 4, using combined DOC + DPF				
Fuel Capacity	gal (liters)	9.3 (35)				
Transmission Type		Mechanical synchronized shuttle			Hydrostatic (HST)	
Main Clutch		Dry single disc, operated via left side foot pedal			None	
Speeds		12 forward x 12 reverse (4 gears, 3 ranges)			3-ranges	
Shuttle Type		Synchronized, with left hand shuttle lever			Side-by-side pedals	
Differential Lock		Mechanical, heel pedal				
Rear Brakes		Wet disc brakes with suspended R and L pedals				
Front Axle Type		4wd with mechanical engagement, 62-degree steering angle				
Rear PTO Type		Independent, electronically engaged, 540 and 540e standard				
Hydraulic System		Open center system				
Hyd. Flow at Remotes	gpm (lpm)	8.9 (34)	11.1 (42)			
Loader Joystick		Standard with 2 mid-mount valves				
Rear Remote Valves		0 standard, 2 optional			2 standard	
3-pt Type		Category I with telescopic stabilizers and lower links				
3-pt Lift Capacity	lb (kg)	3,306 (1500) at ball ends; 2,425 (1100) at 24"				
Operator's Area		Folding ROPS			Cab with HVAC; 2 doors	
Seat and Steering		Adjustable vinyl seat; tilt steering				
Overall Length	in (mm)	130 (3300)				
Wheelbase	in (mm)	70.9 (1800)				
Height over ROPS/Cab	in (mm)	94 (2390)	96 (2440)	97 (2460)		
Base Weight	lb (kg)	4,053 (1840)	4,118 (1870)	4,442 (2015)	4,300 (1950)	4,350 (1975)

Loader Model		160C	180C
Max. Lift Height Under Level Bucket	in (mm)	92.5 (2350)	101 (2565)
Lift Capacity to Max. Height 19.5" Forward of Pivot	lb (kg)	2,361 (1070)	2,628 (1192)
Breakout Force 19.5" Forward of Pivot	lb (kg)	2,985 (1354)	3,711 (1683)
Rollback Force 31.5" Forward of Pivot	lb (kg)	4,098 (1858)	5,721 (2595)
Compatible Tractor Models		X1.35	X1.45 X1.45C X1.45HC X1.55HC

